

OilPRO MINI⁺ - Turnkey

DOUBLE WALL RELIABLE STORAGE

BUILT WITH SAFETY AND THE ENVIRONMENT IN MIND

Following the North American success of TECALEMIT's Lube Oil platform, better and more efficient turnkey solutions are now being introduced. Meet the new OilPRO Mini+ – a full, turnkey solution that speaks value, performance, and reliability. This is an ideal solution that allows easier handling, greater stability, and facilitates access to tight spaces. Double wall construction provides peace of mind, starting with a leakproof outer tank, weld-free galvanized steel, roll-seamed with an oil and fire-resistant seal. The inner tank is blow-molded, with HDPE that is seamless and leakproof.

Save time and resources by selecting TECALEMIT's proven PK3HD & PK5HD oil pumps, the key components behind this new package.

PK3HD/PK5HD PUMP OPTION

TECHNICAL SPECIFICATIONS & FEATURES



Available pump options:	3:1/5:1
Air inlet pressure:	30-150 psi
Fluid pressure:	450 psi/750 psi
Flow rate:	5.28 gpm/4 gpm
Air inlet size:	¼" NPT (F)
Fluid outlet size:	½" (M)

DIGITAL METERED NOZZLE

TECHNICAL SPECIFICATIONS & FEATURES



Inlet connection:	½"
Pressure range:	7-725 psi
Temperature:	14°F to 140°F
Accuracy:	+/- 0.5%
Rigid tube Manual tip Digital meter	
PART # 1781501	

PART #	DESCRIPTION
OIL-31	LUBE PUMP PACKAGE 3:1, NO TANK
OIL-51	LUBE PUMP PACKAGE 5:1, NO TANK



2258

NFPA® 31
CSA
B-139-04



TECHNICAL SPECIFICATIONS & FEATURES

Hose length:	50 ft.
Hose size:	½"
Working pressure:	2320 psi/160 bar
Hose material:	S.A.E. 100R1 wire braid
Weight:	64.8 lbs.
PART # M860154	



DIGITAL METERED NOZZLE

TECHNICAL SPECIFICATIONS & FEATURES

Inlet connection:	½"
Pressure range:	7-1000 psi
Temperature:	14°F to 140°F
Accuracy:	+/- 0.5%
Rigid tube Manual tip Digital meter	
PART # 18133513	



PART #	DESCRIPTION
OIL-31-P	LUBE PUMP PACKAGE 3:1, NO TANK
OIL-51-P	LUBE PUMP PACKAGE 5:1, NO TANK

OilPRO MINI⁺ - Turnkey

TECHNICAL SPECIFICATIONS

BUILT WITH SAFETY AND THE ENVIRONMENT IN MIND

Each tank undergoes thorough testing, including ultra-sound and pressure testing, to ensure optimal thickness and sealing.



- DOUBLE WALL DESIGN**
Uniquely designed tanks are the safest and most reliable double wall set ups on the market.



- SLIM FOOTPRINT**
Slim design makes it more flexible for product placement and overall handling of these packages.



- CLOSED LOOP SYSTEM**
Maintaining product integrity for overall best performance and on road reliability of your vehicles.



- OIL PUMP**
This package would not be complete without the PK3HD or the PK5HD pump. Always outperforming the competition.



- WARRANTY**
Oil Pro Mini⁺ double wall tanks come with a generous 30 year limited warranty.

TANK MODEL	165 Gal/620 L	275 Gal/1000 L	400 Gal/ 1500 L
NOM. CAPACITY US GAL (LITERS)	165 (620)	275 (1000)	400 (1500)
LENGTH INCHES (CM)	29 (74)	43 (110)	64 (163)
WIDTH INCHES (CM)	28 (72)	28 (72)	30 (77)
HEIGHT INCHES (CM)	61 (155)	61 (155)	68 (173)
MIN. HEIGHT REQUIRED INCHES (CM)	66 (168)	66 (168)	76 (193)
TANK WEIGHT LBS. (KG)	132 (65)	167 (76)	333 (151)

