

OIL MANAGEMENT SYSTEM

Keep an eye on levy and inventory control and switch to the new wireless TECALEMIT oil management system "TMS smart". Optimize your inventory control, maximize your profit and benefit from complete control with maximum flexibility and reliability.

As a standalone system or connected to an existing dealer management system (DMS) - the TMS smart family, combined with our myTecalemit fill level monitoring, offers you the most modern oil inventory monitoring and dispensing system currently available on the market.

TECHNICAL SPECIFICATIONS & FEATURES

Viscosity range 20 - 2000 mPa s Smallest volume flow Q min 0.2 gpm Largest volume flow Q ma x +/- 2.5 gpm Max. Operating pressure p 70 bar Threaded connection G 1/2" internal Measuring accuracy +/- 1% (+/-0.5% following calibration) Weight 3.7 Lbs IP protection IP54 Permitted operating temperature 14°F to +131°F Permitted storage temperature -4°F to +158°F Authorized liquids Engine oil, gear oil, hydraulic oil, radiator antifreeze, diesel, heating oil

TMS smart
Gateway



Your advantages at a glance:

- One system for mobile and stationary application
- Simple installation
- Fast and easy operation
- Precise measurement and dispensing
- Full control via "TMS smart Control" software
- Fast payback with price advantage over conventional systems
- Can be easily integrated into existing systems


TMS smart Gateway

The central communication and control unit manages the data processing and controls the communication among the devices.





TMS smart - System layout overview



meter. Operating, measuring and

dispensing unit for oils and radia-

tor antifreeze.

Independent of the end device.

Software works on the gateway.

No PC-installation required.

TECALEMIT

Installation example scheme

